ET150 3963184 US

Docket No. AUS920010108US1

METHOD AND APPARATUS FOR PRESENTING 3-DIMENSIONAL OBJECTS TO VISUALLY IMPAIRED USERS

CROSS REFERENCE TO RELATED APPLICATIONS

5

The present invention is related to an application entitled *Apparatus to Convey Depth Information in Graphical Images and Method Therefor*, serial no. 09/814,397, attorney docket no. AUS9-2001-0094-US1, filed
10 March 21, 2001, assigned to the same assignee, and incorporated herein by reference.

BACKGROUND OF THE INVENTION

15 **1. Technical Field:**

The present invention relates generally to an improved data processing system, and in particular to a method and apparatus for processing graphical data. Still more particularly, the present invention provides a
20 method, apparatus, and computer program for presenting 3-dimensional objects to a visually impaired user.

2. Description of Related Art:

The Internet, also referred to as an "internetwork",
25 is a set of computer networks, possibly dissimilar, joined together by means of gateways that handle data transfer and the conversion of messages from the sending network to the protocols used by the receiving network (with packets if necessary). When capitalized, the term "Internet"
30 refers to the collection of networks and gateways that use the TCP/IP suite of protocols.

The Internet has become a cultural fixture as a

Docket No. AUS920010108US1

source of both information and entertainment. Many
businesses are creating Internet sites as an integral part
of their marketing efforts, informing consumers of the
products or services offered by the business or providing

5   other information seeking to. engender brand loyalty. Many
federal, state, and local government agencies are also
employing Internet sites for informational purposes,
particularly agencies, which must interact with virtually
all segments of society such as the Internal Revenue

10   Service and secretaries of state. Providing informational
guides and/or searchable databases of online public
records may reduce operating costs. Further, the Internet
is becoming increasingly popular as a medium for
commercial transactions.

15   Currently, the most commonly employed method of
transferring data over the Internet is to employ the World
Wide Web environment, also called simply "the Web". Other
Internet resources exist for transferring information,
such as File Transfer Protocol (FTP) and Gopher, but have

20   not achieved the popularity of the Web. In the Web
environment, servers and clients effect data transaction
using the Hypertext Transfer Protocol (HTTP), a known
protocol for handling the transfer of various data files
(e.g., text, still graphic images, audio, motion video,

25   etc.). The information in various data files are
formatted for presentation to a user by a standard page
description language, the Hypertext Markup Language
(HTML). In addition to basic presentation formatting,
HTML allows developers to specify "links" to other Web

30   resources identified by a Uniform Resource Locator (URL).
A URL is a special syntax identifier defining a
communications path to specific information. Each logical
block of information accessible to a client, called a

Docket No. AUS920010108US1

"page" or a "Web page", is identified by a URL. The URL
provides a universal, consistent method for finding and
accessing this information, not necessarily for the user,
but mostly for the user's Web "browser". A browser is a

5 program capable of submitting a request for information
identified by an identifier, such as, for example, a URL.
A user may enter a domain name through a graphical user
interface (GUI) for the browser to access a source of
content. The domain name is automatically converted to

10 the Internet Protocol (IP) address by a domain name system
(DNS), which is a service that translates the symbolic
name entered by the user into an IP address by looking up
the domain name in a database.

Visually impaired users of the Web often rely on

15 tools, such as a talking Web browser. An example of a
talking web browser is the Home Page Reader (HPR), which
is available from International Business Machines
Corporation (IBM). HPR is a spoken on-ramp to the
information highway for computer users who are blind or

20 visually impaired. HPR provides Web access by quickly,
easily, and efficiently speaking Web page information.
HPR provides a simple, easy-to-use interface for
navigating and manipulating Web page elements. Using the
keyboard to navigate, a user who is blind or who has a

25 visual impairment can hear the full range of Web page
content provided in a logical, clear, and understandable
manner.

A Web page typically includes content using
different types of media. In addition to text, audio and

30 graphical images may be included. The text in a Web page
may be spoken using HPR. Audio portions of the Web page
are perceivable by a visually impaired user. On the
other hand, images, especially 3-dimensional images, in

Docket No. AUS920010108US1

these Web pages are inaccessible to a visually impaired user.

Therefore, it would be advantageous to have an improved method and apparatus for presenting
5   3-dimensional images to a visually impaired user.

Docket No. AUS920010108US1

SUMMARY OF THE INVENTION

5   The present invention provides for a method and
apparatus for examining a three dimensional image in a
data processing system. An object is presented, wherein
the object includes a set of views for different angles
of view for the object. In response to a user input to
10   traverse a view from the set of views, a depth map is
transcoded for the view into a non-visual output. In
response to other user inputs to present other views from
the set of views, depth maps from those views are
transcoded into non-visual outputs. In this manner, a
15   visually impaired user is able to perceive a
3-dimensional object.

Docket No. AUS920010108US1

BRIEF DESCRIPTION OF THE DRAWINGS

5   The novel features believed characteristic of the
invention are set forth in the appended claims. The
invention itself, however, as well as a preferred mode of
use, further objectives and advantages thereof, will best
be understood by reference to the following detailed
description of an illustrative embodiment when read in
10   conjunction with the accompanying drawings, wherein:

Figure 1 is a pictorial representation of a network
of data processing systems in which the present invention
may be implemented;

Figure 2 is a block diagram of a data processing
15   system that may be implemented as a server in accordance
with a preferred embodiment of the present invention;

Figure 3 is a block diagram illustrating a data
processing system in which the present invention may be
implemented;

20   **Figure 4** is a diagram of components in a network
data processing system used to present 3-dimensional
objects to a visually impaired user in accordance with a
preferred embodiment of the present invention;

Figure 5 is a diagram illustrating components in a
25   data processing system used to present a 3-dimensional
object to a visually impaired user in accordance with a
preferred embodiment of the present invention;

Figure 6 is a diagram of a Web page with a
3-dimensional object in accordance with a preferred
30   embodiment of the present invention;

Docket No. AUS920010108US1

Figure 7 is a diagram of a depth map of a front view of an object in accordance with a preferred embodiment of the present invention;

Figure 8 is a diagram of a depth map for a top view of an object in accordance with a preferred embodiment of the present invention;

Figure 9 is a flowchart of a process used for presenting a 3-dimensional object in accordance with a preferred embodiment of the present invention; and

Figure 10 is a flowchart of a process used for transcoding or scanning a depth map of an image in accordance with a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the figures, **Figure 1** depicts a
pictorial representation of a network of data processing
5   systems in which the present invention may be implemented.
Network data processing system **100** is a network of
computers in which the present invention may be
implemented. Network data processing system **100** contains
a network **102**, which is the medium used to provide
10   communications links between various devices and computers
connected together within network data processing system
100. Network **102** may include connections, such as wire,
wireless communication links, or fiber optic cables.

In the depicted example, server **104** is connected to
15   network **102** along with storage unit **106**. In addition,
clients **108**, **110**, and **112** are connected to network **102**.
These clients **108**, **110**, and **112** may be, for example,
personal computers or network computers. In the depicted
example, server **104** provides data, such as boot files,
20   operating system images, and applications to clients
108-112. Clients **108**, **110**, and **112** are clients to server
104. Network data processing system **100** may include
additional servers, clients, and other devices not shown.
In the depicted example, network data processing system
25   **100** is the Internet with network **102** representing a
worldwide collection of networks and gateways that use the
TCP/IP suite of protocols to communicate with one another.
At the heart of the Internet is a backbone of high-speed
data communication lines between major nodes or host
30   computers, consisting of thousands of commercial,
government, educational and other computer systems that
route data and messages. Of course, network data

Docket No. AUS920010108US1

processing system **100** also may be implemented as a number
of different types of networks, such as for example, an
intranet, a local area network (LAN), or a wide area
network (WAN). **Figure 1** is intended as an example, and not

5   as an architectural limitation for the present invention.

Referring to **Figure 2**, a block diagram of a data
processing system that may be implemented as a server,
such as server **104** in **Figure 1**, is depicted in accordance
with a preferred embodiment of the present invention.

10   Data processing system **200** may be a symmetric
multiprocessor (SMP) system including a plurality of
processors **202** and **204** connected to system bus **206**.
Alternatively, a single processor system may be employed.
Also connected to system bus **206** is memory

15   controller/cache **208**, which provides an interface to local
memory **209**. I/O bus bridge **210** is connected to system bus
206 and provides an interface to I/O bus **212**. Memory
controller/cache **208** and I/O bus bridge **210** may be
integrated as depicted.

20   Peripheral component interconnect (PCI) bus bridge
214 connected to I/O bus **212** provides an interface to PCI
local bus **216**. A number of modems may be connected to PCI
local bus **216**. Typical PCI bus implementations will
support four PCI expansion slots or add-in connectors.

25   Communications links to network computers **108-112** in
Figure 1 may be provided through modem **218** and network
adapter **220** connected to PCI local bus **216** through add-in
boards.

Additional PCI bus bridges **222** and **224** provide

30   interfaces for additional PCI local buses **226** and **228**,
from which additional modems or network adapters may be
supported. In this manner, data processing system **200**

Docket No. AUS920010108US1

allows connections to multiple network computers. A
memory-mapped graphics adapter **230** and hard disk **232** may
also be connected to I/O bus **212** as depicted, either
directly or indirectly.

5   Those of ordinary skill in the art will appreciate
that the hardware depicted in **Figure 2** may vary. For
example, other peripheral devices, such as optical disk
drives and the like, also may be used in addition to or in
place of the hardware depicted. The depicted example is

10   not meant to imply architectural limitations with respect
to the present invention.

      The data processing system depicted in **Figure 2** may
be, for example, an IBM e-Server pSeries system, a
product of International Business Machines Corporation in

15   Armonk, New York, running the Advanced Interactive
Executive (AIX) operating system or LINUX operating
system.

      With reference now to **Figure 3**, a block diagram
illustrating a data processing system is depicted in which

20   the present invention may be implemented. Data processing
system **300** is an example of a client computer. Data
processing system **300** employs a peripheral component
interconnect (PCI) local bus architecture. Although the
depicted example employs a PCI bus, other bus

25   architectures such as Accelerated Graphics Port (AGP) and
Industry Standard Architecture (ISA) may be used.
Processor **302** and main memory **304** are connected to PCI
local bus **306** through PCI bridge **308**. PCI bridge **308** also
may include an integrated memory controller and cache

30   memory for processor **302**. Additional connections to PCI
local bus **306** may be made through direct component
interconnection or through add-in boards. In the depicted

Docket No. AUS920010108US1

example, local area network (LAN) adapter **310**, SCSI host bus adapter **312**, and expansion bus interface **314** are connected to PCI local bus **306** by direct component connection. In contrast, audio adapter **316**, graphics

5   adapter **318**, and audio/video adapter **319** are connected to PCI local bus **306** by add-in boards inserted into expansion slots. Expansion bus interface **314** provides a connection for a keyboard and mouse adapter **320**, modem **322**, and additional memory **324**. Small computer system interface

10 (SCSI) host bus adapter **312** provides a connection for hard disk drive **326**, tape drive **328**, and CD-ROM drive **330**. Typical PCI local bus implementations will support three or four PCI expansion slots or add-in connectors.

An operating system runs on processor **302** and is used

15 to coordinate and provide control of various components within data processing system **300** in **Figure 3**. The operating system may be a commercially available operating system, such as Windows 2000, which is available from Microsoft Corporation. An object oriented programming

20 system such as Java may run in conjunction with the operating system and provide calls to the operating system from Java programs or applications executing on data processing system **300**. "Java" is a trademark of Sun Microsystems, Inc. Instructions for the operating system,

25 the object-oriented operating system, and applications or programs are located on storage devices, such as hard disk drive **326**, and may be loaded into main memory **304** for execution by processor **302.**

Those of ordinary skill in the art will appreciate

30 that the hardware in **Figure 3** may vary depending on the implementation. Other internal hardware or peripheral devices, such as flash ROM (or equivalent nonvolatile

Docket No. AUS920010108US1

memory) or optical disk drives and the like, may be used in addition to or in place of the hardware depicted in **Figure 3**. Also, the processes of the present invention may be applied to a multiprocessor data processing
5 system.

As another example, data processing system **300** may be a stand-alone system configured to be bootable without relying on some type of network communication interface, whether or not data processing system **300** comprises some
10 type of network communication interface. As a further example, data processing system **300** may be a Personal Digital Assistant (PDA) device, which is configured with ROM and/or flash ROM in order to provide nonvolatile memory for storing operating system files and/or
15 user-generated data.

The depicted example in **Figure 3** and above-described examples are not meant to imply architectural limitations. For example, data processing system **300** also may be a notebook computer or hand held computer in
20 addition to taking the form of a PDA. Data processing system **300** also may be a kiosk or a Web appliance.

With reference now to **Figure 4**, a diagram of components in a network data processing system used to present 3-dimensional objects to a visually impaired user
25 is depicted in accordance with a preferred embodiment of the present invention. In these examples, images of 3-dimensional objects are incorporated into presentations in Web pages.

Web server **400** may send a Web page to client **402**
30 across Internet **404**. The Web page is received at browser **406** for presentation. In the case of a visually impaired user, browser **406** may be a talking Web browser. A

Docket No. AUS920010108US1

browser is an application used to navigate or view information or data in a distributed database, such as the Internet or the World Wide Web. In this example, browser **406** is a talking Web browser, which may be

5   implemented using the Home Page Reader HPR, which is available from International Business Machines Corporation (IBM). In these examples, browser **406** includes a user interface, which includes both a graphical user interface (GUI) and a "visually impaired

10   interface". The GUI allows a normal user to interface or communicate with browser **406**, while the visually impaired interface provides a means for a visually handicapped user to navigate a Web page. This visually impaired interface includes an interface that will recognize voice

15   commands as well as commands input from a keyboard.

Most forms of media are presented directly by browser **406**. In the depicted examples, however, 3-dimensional images are presented in conjunction with 3-dimensional depth map analyzer **408**. In the depicted

20   examples, 3-dimensional depth map analyzer **408** is shown as a separate component from browser **406** for purposes of illustration. This analyzer may be implemented in various ways, such as a plug-in or as a process within browser **406**.

25   The output is typically presented to a user through assistive technology device **410**. In many cases, this device is an audio device, but it also may encompass other types of devices, such as a device generating tactile output like Braille.

30   With respect to 3-dimensional objects, solid modeling involves representing objects as solids using a variety of mechanisms to represent the surface, inside,

Docket No. AUS920010108US1

and outside of a 3-dimensional object. Solid modeling techniques are widely used in computer aided design and graphics. The present invention makes use of depth maps, which are maps of 3-dimensional scenes. Basically, a

5   depth map is a 2-dimensional coordinate showing at each coordinate position the distance of a 3-dimensional scene point. For example, in a depth map a projected 2-dimensional coordinate corresponding to a distant mountain may have a value of 1000 feet, while a projected

10 2-dimensional coordinate corresponding to a nearby building may have a value of 100 feet. These types of depth maps are well known to those of ordinary skill in the art and may be constructed using stereographic cameras or with a single moving camera. By calculating

15 the movement of pixels of multiple images, a mathematical construction can be made of the depths of various points.

The present invention provides a method, apparatus, and computer program to allow a visually impaired user to traverse or walk in a "virtual" fashion around an object.

20 Solid modeling techniques are used to capture the view of the object from different angles. The different views are sent, in these examples, by Web server **400** to browser **406** with a Web page. The different views may be transcoded or presented using depth maps and texture maps

25 to present the object to the visually impaired user through a non-visual output. This type of output may be, for example, a tactile sensation or an audio presentation of the object to a visually impaired user.

Turning next to **Figure 5**, a diagram illustrating

30 components in a data processing system used to present a 3-dimensional object to a visually impaired user is depicted in accordance with a preferred embodiment of the

Docket No. AUS920010108US1

present invention. Object **500** represents a 3-dimensional
object that a visually impaired user desires to perceive.
In this example, the visually impaired user is presented
with menu **502** identifying directions in which the object

5   may be viewed. This menu is presented in response to a
user input, such as a "right click" of a mouse button or
thorough some other input. Although menu **502** is
presented as a pop-up menu, this menu may be traversed
with a talking Web browser to audibly present the

10   different options. For example, front **504** or top **506** may
be selected. Based on these selections, one of depth
maps **508**, **510**, and **512** may be processed by 3-dimensional
depth map analyzer **514** for presentation through assistive
technology device **516**. For example, depth map **508** may

15   represent a front view of object **500**, while depth map **510**
represents a top view of object **500**. Other depth maps
may present other views, such as, for example, a bottom
view, a back view, or other views from different angles
of object **500**. The depth map may be presented on the

20   browser with the non-visual presentation be generated
based on the user traversing the depth map.

The transcoding of depth map values is performed by
3-dimensional depth map analyzer **514**. In the case of
transcoding depth map value for an audio presentation,

25   the values are transcoded or converted into audio
signals. Parameters of an audio signal may be varied to
provide an identification of different depths, such as,
for example, pitch or intensity of an audio signal. For
example, if the depth of a point is 20 feet, the

30   transcoded audio signal may be presented at 60 decibels
(dB). If the depth is at 10 feet, the audio signal may
be presented at 70 dBs. The mapping of the depth to

Docket No. AUS920010108US1

audio volume need not be linear and could be logarithmic. Similar types of transcoding may be performed for tactile presentations.

With reference now to **Figure 6**, a diagram of a Web
5 page with a 3-dimensional object is depicted in accordance with a preferred embodiment of the present invention. As illustrated, browser **600** displays Web page **602** in which object **604** is present. Object **604** is a 3-dimensional object with different angles or
10 perspective, which may be viewed through pop-up menu **606**. In this case, object **604** is a cylinder. In this example, pop-up menu **606** allows a front view, a top view, or a change in presentation of the present view by 10 degrees.

With reference to **Figure 7**, a diagram of a depth map
15 of a front view of an object is depicted in accordance with a preferred embodiment of the present invention. In this example image **700** is a front view of object **604**, a cylinder, in **Figure 6**. Depth map **702** provides values for different portions for image **700**. Depth map **702** is
20 transcoded by a 3-dimensional depth map analyzer, such as 3-dimensional depth map analyzer **514** in **Figure 5**, to present the front view of object **604**. The values of image **700** are 30 for the background, while the values for the cylinder range from 10 to 8 and back to 10 going from
25 left to right to illustrate the curve of the cylinder.

With reference now to **Figure 8**, a diagram of a depth map for a top view of an object is depicted in accordance with a preferred embodiment of the present invention. In the depicted examples, image **800** is a top view of object
30 **604** in **Figure 6**. Depth map **802** provides values for image **800**. The background portion of image **800** is represented using values of 15, while the top of object **604** is

Docket No. AUS920010108US1

represented using values of 5.

Figures 7 and **8** are presented for purposes of illustration to show different views of a 3-dimensional object, which may be presented to a visually impaired

5　user, in a non-visual manner. Other views, such as a back view, a bottom view, and views from other angles may be presented using depth maps to provide a visually impaired user with a presentation of the 3-dimensional object.

10　Turning next to **Figure 9**, a flowchart of a process used for presenting a 3-dimensional object is depicted in accordance with a preferred embodiment of the present invention. The process illustrated in **Figure 9** may be implemented as a computer program or other code for

15　execution by a processor. More specifically, the process may be implemented in browser **406** and 3-dimensional depth map analyzer **408** in **Figure 4**.

The process begins by identifying a 3-dimensional object (step **900**). Next, options for different views of

20　the 3-dimensional object are presented to a user (step **902**). In these examples, the options are presented in a pop-up menu as described above. Then, user input is received (step **904**). A determination is made as to whether the user input indicates that a new view has been

25　selected by the user (step **906**). If the user input indicates that a new view has been selected, a new view is obtained (step **908**) with the process returning to step **904.**

Turning back to step **906**, if a new view has not been

30　selected, a determination is made as to whether the user input indicates that the view is to be scanned (step **910**). If the answer to this determination is yes, then

Docket No. AUS920010108US1

the depth map image is scanned (step **912**). This scanning
is performed by a 3-dimensional depth map analyzer, in
these examples. Next, output data is generated from
processing of the depth map in step **912** for a non-visual
5   presentation (step **914**). This data may be, for example,
different volume levels for different depths in the
portion of the depth map scanned in response to the user
input. The data is then presented to the user (step **916**)
with the process returning to step **904**. As described
10   above, this presentation may take many different forms,
such as audio or tactile.

      Turning back to step **910**, if the view is not to be
scanned, a determination is made as to whether the
viewing of 3-dimensional object ends (step **920**). If it
15   is determined that the viewing ends, the process
terminates. Otherwise, the process proceeds to step **916**
as described above.

      With reference now to **Figure 10**, a flowchart of a
process used for transcoding or scanning a depth map of
20   an image is depicted in accordance with a preferred
embodiment of the present invention. The process
illustrated in **Figure 10** is a more detailed description
of step **912** in **Figure 9**.

      The process begins by identifying an image for
25   processing (step **1000**). Next, a determination is made as
to whether a depth map is present for the image (step
1002). In the case of receiving a Web page from a
server, depth maps for a 3-dimensional object may be made
available from the server.
30   If a depth map is present, the depth map is
retrieved from the server (step **1004**). The portion of
the depth map scanned by the user input is identified for

Docket No. AUS920010108US1

presentation (step **1006**) with the process terminating
thereafter. If depth map is not present for the image, a
determination is made as to whether stereo/motion picture
frames are present for the image (step **1008**). If the
5   answer to this determination is yes, a depth map is
generated (step **1010**) with the process proceeding to step
1006 as described above. If stereo/motion picture frames
are absent, a determination is then made as to whether an
equation is present for the image (step **1012**). If an
10   equation is absent, the process terminates. Otherwise, a
depth map is generated from the equation (step **1014**) with
the process proceeding to step **1006** as described above.

      Thus, the mechanism of the present invention allows
for a visually impaired user to obtain a non-visual
15   presentation of a 3-dimensional object. When a tactile
output is generated, the visually impaired user may
obtain a qualitative tactile presentation of the object
in a manner analogues to using ones hands to touch
objects. The depth of different portions of an object
20   also may be presented in an audible manner in which
different parameters of an audio signal are varied to
provide an identification of the depth of different
portions of an object. These 3-dimensional views are
presented through the use of depth maps. Of course the
25   data also may be obtain in other ways, such as through
the use of an equation describing an object or through
other maps, such as a contour map.

      It is important to note that while the present
invention has been described in the context of a fully
30   functioning data processing system, those of ordinary
skill in the art will appreciate that the processes of
the present invention are capable of being distributed in

Docket No. AUS920010108US1

the form of a computer readable medium of instructions, and a variety of forms and that the present invention applies equally regardless of the particular type of signal bearing media actually used to carry out the

5   distribution. Examples of computer readable media include recordable-type media, such as a floppy disk, a hard disk drive, a RAM, CD-ROMs, DVD-ROMs, and transmission-type media, such as digital and analog communications links, wired or wireless communications

10 links using transmission forms, such as, for example, radio frequency and light wave transmissions. The computer readable media may take the form of coded formats that are decoded for actual use in a particular data processing system.

15   The description of the present invention has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in

20 the art. The embodiment was chosen and described in order to best explain the principles of the invention, the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are

25 suited to the particular use contemplated.